



TOP MOUNT FILTER (TM SERIES)


Features :

Top Mount Sand Filters are manufactured with high grade fiberglass & resins utilizing the latest engineering techniques ensuring high quality and superior strength for long life & durability.

- .High Rate Sand Filter
- .Heavy duty UV resistant fiber glass
- .Resistant to chemicals & corrosion
- . Sight glass for inspection of filtered water
- .Sand drain plug for easier sand removal



Code	Model	Size (Inches)	Design Flow m ³ /h	Filtration Area m ²	Pipe Size Inch	Sand Required Kg
980101	PF-350	14"	5.0	0.09	1.5	30
980102	PF-400	16"	7.0	0.13	1.5	40
980103	PF-450	18"	8.0	0.16	1.5	60
980104	PF-525	21"	11.5	0.22	1.5	75
980105	PF-625	25"	16.4	0.30	1.5	160
980106	PF-700	28"	21.5	0.40	1.5	210
980107	PF-750	30"	25.2	0.45	2.0	270
980108	PF-800	32"	26.8	0.55	2.0	370
980109	PF-900	36"	30.2	0.64	2.0	500
980110	PF -1050	42"	43.0	0.85	2.0	850
980111	PF-1200	48"	51.0	1.13	2.0	1100



TM Series Bobbin Wound Sand Filter

PRODUCT DIMENSION

	PF-350	PF-400	PF-450	PF-525	PF-625	PF-700	PF-750	PF-800	PF-900	PF-1050	PF-1200
A	350	400	450	525	625	700	750	800	900	1050	1200
B	430	490	580	610	710	750	820	880	980	1140	1160
C	726	757	835	980	980	1010	1030	1170	1260	1380	1450